

# **Coastal and Near Surface Mixing**

Rolf Lueck  
Centre for Earth and Ocean Research  
University of Victoria  
Victoria, B.C., V8W 2Y2  
phone: (250) 721-8918 fax: (250) 721-6195 email: [rlueck@uvic.ca](mailto:rlueck@uvic.ca)

Award Number: N00014-03-1-0616  
<http://seos.uvic.ca>

## **LONG-TERM GOAL**

My long-term goal is to contribute to our understanding of turbulence and mixing processes in the ocean, and to establish how mixing affects the distribution and transport of heat, salt, and other important physical processes.

## **OBJECTIVES**


I wish to establish how the efficiency and the rate of mixing depend upon the shear in currents, the stratification of the density, and the intensity of turbulence. Mixing increases the potential energy of the ocean by raising denser water towards the surface. The efficiency of mixing is the fraction of kinetic energy that is converted to potential energy. The challenge is to measure the mixing directly without relying on models and assumptions about the nature of turbulence.

Sound is backscattered from turbulence and plankton. I want to relate the intensity of turbulence to the backscattering cross-section through the simultaneous measurement of both in the ocean, and to determine the features of the back-scatter that distinguish turbulence from plankton. In addition I would like to use the backscatter to determine the spatial distribution of plankton on scales of 0.1 to 10 m with particular interest in clustering.

## **APPROACH**

We are using a towed vehicle to survey the turbulence in deep tidal channels where, over the course of a tidal cycle, currents, stratification and the intensity of turbulence vary considerably. The towed vehicle (Fig. 1) carries high-resolution velocity and temperature sensors (shear probes and thermistors), current meters, a vertical array of three pairs of salinity and temperature sensors, and motion sensors. These sensors provide a measure of the density stratification, the rate of dissipation of turbulent kinetic energy, and the fluctuations of vertical velocity, salinity and temperature due to turbulent eddies. Simultaneously, we measure the vertical gradient of current using a ship-mounted acoustic current sensor (ADCP), and take profiles of salinity, temperature and density over the full water column using a CTD lowered from the tow-ship. The correlation of the fluctuations of vertical velocity with temperature and salinity provides a direct estimate of the vertical flux of density (hence the rate of mixing) without making any assumptions about the nature of turbulence. The ratio of this flux to the rate of dissipation of kinetic energy gives the efficiency of mixing.

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>SEP 2003</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-2003 to 00-00-2003</b>	
4. TITLE AND SUBTITLE <b>Coastal and Near Surface Mixing</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Centre for Earth and Ocean Research,,University of Victoria,Victoria, B.C., V8W 2Y2, , ,</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT <b>My long-term goal is to contribute to our understanding of turbulence and mixing processes in the ocean, and to establish how mixing affects the distribution and transport of heat, salt, and other important physical processes.</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>7</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			




**Fig. 1. The towed vehicle TOMI used for the studies in Sansum Narrows and Knight Inlet. Details of the acoustic transducers are shown in Fig. 2. Four of the six microstructure probes on the nose of the instrument measure velocity fluctuations (shear probes, P1-4) and the other two measure temperature fluctuations (FP07 thermistors, T1-2). One set of the three SeaBird conductivity (salinity) and temperature sensors is mounted close to the shear probes to determine the covariance of vertical velocity with salinity and temperature. The vehicle is 4.5 m long, weighs 4500 N (5 newtons equals 1 pound)) in air, and has an enclosed mass of 800 kg when submerged. Its underwater weight is only 150 N.**

We have also mounted sounders (44 and 307 kHz) just below the turbulence sensors to project sound pulses forward from the towed vehicle (Fig. 2). These pulses are directed along the tow-path of the vehicle and, thus, we simultaneously measure the acoustic backscatter and the turbulence, and can relate them at all positions along the tow track. Simultaneous, but slightly displaced, measurements of backscatter from vertical sounders on the ship allow us to identify scattering layers and to target our tow path. Periodic vertical net tows are used to identify zooplankton species and their abundance. These data are used to distinguish echos from large individual creatures and clusters of smaller plankton.

## WORK COMPLETED

We have completed two cruises to Sansum Narrows (July 1999; August 2000) and collected a total of 80 hours of data which have been used to estimate the vertical fluxes of heat and salt (hence, density). We have completed one cruise around the sill in Knight Inlet (June 2001), known for its internal

hydraulic jump, and used these data to examine the relationship between turbulence and backscatter, and to explore the relationship between turbulence and zooplankton distribution.




**Fig. 2. The towing arrangement and acoustic insonification during tows over the Knight Inlet sill. The towed vehicle is typically one to two hundred meters behind the tow ship. Inset: close up view of the sounders and turbulence sensors.**

## RESULTS


The upper panel of Fig. 3A shows a section of acoustic backscatter derived from sounders mounted on the tow ship as it travels over the edge of the sill in Knight Inlet. The backscatter intensity is color coded from weak to strong by blue to red, respectively. The backscatter makes visible a lee wave that was descending from 15 to 35 m. The pair of white lines depict the path of the tow-vehicle, which crosses through this lee wave. The lower panel in Fig. 3B shows the backscatter as seen by the sounders on the tow-vehicle for a short section of the tow. The horizontal axis is time increasing towards the right while the vertical axis gives the range of echos from ahead of the vehicle. The temperature microstructure gradient, as measured by a turbulence sensor on the nose of the vehicle, is drawn below the sonogram. The turbulence is intermittent or patchy. The turbulence is first detected through the backscatter (when the turbulence is weak at the location of the sensors and acoustic sounders) and is detected by the turbulence sensors when the nose of the vehicle enters into the patches. The vehicle is traveling about 1 m/s, and so, the turbulence is measured by the temperature sensors less than 20 seconds after patches are detected by the sounders.

Backscatter from regions of weak turbulence but high zooplankton concentration is very different from echos obtained in regions of strong turbulence. The echos indicate clustering (or aggregation) of zooplankton with typical horizontal scales of 0.2 m (Fig. 4). The typical separation between clusters is about 1 m with most variations confined to 0.5 to 2 m spacing. Ship mounted sounders inevitably have a large footprint due to the long range of the targets. Thus, layers which appear continuous in sonograms from ship-mounted sounders are, in reality, clusters of plankton as revealed by the short-range echograms produced with the sounders mounted on the towed vehicle.



*Fig. 3. Section of acoustic backscatter over the edge of the sill in Knight Inlet collected with ship-based echo sounders (upper panel, A). The white lines indicate the path of the towed vehicle which was traveling 25 to 30 m below the surface. The lower panel (B) is the backscatter detected with the sounders mounted on the towed vehicle from the time that the vehicle was traveling just below the lee wave over the sill. The lower trace gives the temperature microstructure detected by one sensor on the nose of the vehicle.*





*Fig. 4. The acoustic backscatter as reported by the ship-mounted 100kHz sounder. The yellow band between depths of 30 and 70 m is the acoustic backscatter from zooplankton. Turbulence sensors on the towed vehicle reported no signals in this depth range. The wide line depicts the path of the towed vehicle. The backscatter observed with the forward looking 300 kHz sounder mounted on the towed vehicle is shown in the middle pane from the region just above the zooplankton layer. The blue lines show the width of the acoustic beam which is about 1 m vertical at a range of 10 m. The zooplankton are sparsely distributed with a tendency to ward aggregation. The lower panel shows the backscatter from the middle of the zooplankton layer. The zooplankton are strongly clustered into groups of 0.2 m width and a typical separation of 1 m between groups. The horizontal resolution of the sounder is 0.2 m while the vertical resolution is only  $\sim 1$  m because of the beam width. Thus, the vertical size of the clusters is an artifact of the instrumentation.*

## IMPACT/APPLICATION

Backscatter can be used to detect turbulence and to make quantitative estimates of its strength. Biomass estimates derived from acoustic backscatter may be biased high because this method assumes that all backscatter comes from zooplankton. Our technique also lends itself to the study of the ecologically important issue of the co-occurrence of turbulence and zooplankton.

The spatial distribution of plankton is not diffuse. The zooplankton are clustered with typical sizes of 0.2 m and 1 m spacing. This has significant implications for models of predator-prey interaction, foraging and reproduction.

## TRANSITIONS

The methods and techniques used for the measurement of the heat and salt flux are being transferred to autonomous underwater vehicles (AUVs). See related projects below.

## RELATED PROJECTS

1. Ed Levine of the Naval Undersea Warfare Center and I are using the small autonomous vehicles *REMUS* to study mixing processes in the New Jersey Bight and Massachusetts Bay.
2. Tom Osborn (Johns Hopkins University), Steve Thorpe (South Hampton, UK) and I are using the AUV *Autosub* to examine gravity currents on the continental slope and Langmuir circulation.
3. Manhar Dhanak (Florida Atlantic University) and I are using the *Explorer* AUV to study mixing processes in the Florida Current.
4. Hide Yamazaki (Tokyo University of Fisheries) and I are investigating the effect of islands in the Kuroshio Current south of Tokyo. We are looking at the turbulence, water mass modification, nitrification of the euphotic zone and its biological response in the wake of these islands.

## PUBLICATIONS

Hasegawa, D., H. Yamazaki, R. Lueck, and L. Seuront, 2003, How islands stir and cultivate the ocean, *Nature*. [Submitted]

Ross, T. and R. Lueck, 2003: Sound scattering from oceanic turbulence. *J. Geophys. Res. Let.*, **30**, 76-1 to 76-4. [Published, Refereed]

Thorpe, S. A., T. R. Osborn, J. Jackson, A. J. Hall and R. G. Lueck, 2003: Measurements of turbulence in an upper ocean mixing layer using AUTOSUB. *J. Phys. Oceanogr.*, **33**, 122-145. [Published, Refereed]

Macoun, P. and R. Lueck, 2003: On the wavenumber resolution of shear probes. *J. Atmos. Oceanic Technol.*, in press. [Refereed, in Press]

Lueck, R. G., F. Wolk and H. Yamazaki, 2002: Ocean velocity microstructure measurements in the 20<sup>th</sup> century. *Japan J. of Oceanogr.*, 58, 153-174. [Published, Refereed]